
Injector-Rehab.com

Injector p/n	Vehicle Year Engine	Mazda R	X7		Bryan Sta	hl					
Test		Injector #									
	1	2	3	4	5	6	7	8			
Resistance ohms	3.2	3.2	3.2	3.2							
Leak Test Before	Fail	Fail	Fail	Fail							
Pass / Fail After	Pass	Pass	Pass	Pass							
Spray Pattern Before	Poor	Poor	Poor	Fair							
Spray Pattern After	Fair	Poor	Good	Good							
Static Flow Before	190	188	402	444							
Static Flow After	240	240	456	456							
15 sec @ 2.25 Bar	60	60	114	114							
cc/min @ 2.25 Bar	240	240	456	456							
		Inje	2 Should	not be used	d						



Largest Variance Before 57.658% Largest Variance After 47.368% **Ideal System Balance < 2%

HP Capability (Per Injector)

	B.S.F.C.									
	0.40	0.45	0.50	0.55	0.60	0.65	0.70			
Injector Duty Cycle										
@ 70% Duty	58.0	51.6	46.4	42.2	38.7	35.7	33.1			
@ 75% Duty	62.1	55.2	49.7	45.2	41.4	38.2	35.5			
@ 80% Duty	66.3	58.9	53.0	48.2	44.2	40.8	37.9			
@ 85% Duty	70.4	62.6	56.3	51.2	47.0	43.3	40.2			
@ 90% Duty	74.6	66.3	59.7	54.2	49.7	45.9	42.6			